



**SESC REQUIREMENTS**

ALL CONSTRUCTION SHALL COMPLY WITH THE SOIL EROSION AND SEDIMENTATION CONTROL REQUIREMENTS OF WASHTENAW COUNTY AND THE STATE OF MICHIGAN. PROTECTIVE MEASURES AS SHOWN BELOW SHALL BE PROVIDED AT A MINIMUM AND CONFIRMED WITH LOCAL AGENCY REQUIREMENTS.

ALL TEMPORARY EROSION CONTROL DEVICES SHALL BE REMOVED AFTER PERMANENT GRASS COVER IS ESTABLISHED. TEMPORARY EROSION CONTROL DEVICES SHOULD BE IN PLACE PRIOR TO EXCAVATION TO THE EXTENT POSSIBLE.

- KEY DESCRIPTION**
- ◇ PERMANENT FENCING 6' / PALCH
  - ◇ BILT FENCE

**GENERAL EARTHWORK NOTES:**

1. FOR WORK AT OR ABOVE SUBGRADE ELEVATION, IT IS THE CONTRACTOR'S RESPONSIBILITY TO VERIFY THE REQUIRED EARTHWORK VOLUMES BASED ON THE GRADING PLAN. IF FILL IS REQUIRED, THE CONTRACTOR SHALL INCLUDE THE REQUIRED VOLUME OF IMPORTED CLAM (A ENGINEERED FILL, IF EXCESS SOILS NEED TO BE SPILLED, THE CONTRACTOR SHALL INCLUDE HAULING AND SPILLING SOILS OFF-SITE IN THE BID. NO CONTRACT COST ADJUSTMENTS WILL BE CONSIDERED FOR EARTHWORK REQUIRED TO ACHIEVE THE FINISH GRADING SHOWN.

**BARRIER-FREE NOTES**

BARRIER-FREE PARKING AND ACCESSIBLE ROUTES MUST COMPLY WITH THE AMERICANS WITH DISABILITIES ACT, INCLUDING BUT NOT LIMITED TO THE FOLLOWING:

- 1:12 (IN) MAXIMUM CROSS-SLOPE ON ACCESSIBLE ROUTE.
- NO CHANGES IN LEVEL GREATER THAN 1/4" ALONG ACCESSIBLE ROUTE.
- 1:50 (IN) MAXIMUM LONGITUDINAL SLOPE ON ACCESSIBLE ROUTE (EXCEPT WHERE RAMPIS ARE PROVIDED).
- 1:50 (IN) MAXIMUM SLOPE ON ANY DIRECTION IN BILT PARKING AND ACCESSIBLE AREAS.

**GENERAL NOTES**

1. CALL "1088 DIG" AND VERIFY ALL UNDERGROUND UTILITIES BEFORE EXCAVATION AT THE SITE. ANY UTILITIES DISTURBED BY CONSTRUCTION SHALL BE REPAIRED AT CONTRACTOR'S EXPENSE. USE PRIVATE UTILITY LOCATOR SERVICE FOR ANY UTILITIES 1088 DIG WILL NOT TRACE.
2. ANY DISCREPANCIES BETWEEN THESE PLANS AND ACTUAL FIELD CONDITIONS SHOULD BE REPORTED TO THE OWNER'S REPRESENTATIVE IMMEDIATELY FOR RESOLUTION.
3. EROSION SHALL BE CONTROLLED AS SPECIFIED AND AS REQUIRED BY LOCAL, STATE OR FEDERAL AUTHORITIES HAVING JURISDICTION.
4. ALL DIMENSIONS ARE GIVEN TO OUTSIDE EDGE OF CURB OR EDGE OF PAVEMENT UNLESS OTHERWISE NOTED. ALL RADIUS ARE 9' UNLESS OTHERWISE NOTED.
5. ALL UNPAVED AREAS DISTURBED BY CONSTRUCTION SHALL RECEIVE 6" TOPSOIL AND LAWN FERN SPECIFICATIONS, SUPPLEMENT WITH PROPOSED TOPSOIL AS REQUIRED TO PROVIDE 4" DEPTH.



**Site Design Solutions** LLC  
 Landscape Architecture, Planning and Design Services  
 313 North Burdick Street, Kalamazoo, Michigan 49007  
 (269) 978-5143 (voice) • (269) 983-5060 (toll-free fax)  
 sds@sdsls.com

**SITE PLAN**

**LITTLE LEAGUE FIELD**  
**PEACE LUTHERAN CHURCH**  
**SCIO TOWNSHIP, MICHIGAN**

Revisions


Sheet

**C-1**